



1562-0x

EXHAUST HOSE FOR HOT AIR, SILICONE, SINGLE COATED



Media



SPECIFICATIONS

Cover	Silicone	Media	Ventilation
Tube	Silicone	Temp min	-50 °C
Reinforcement	Steel spiral	Temp max	300 °C
Resistance cover	Abrasion, Weather	Color	Red
Design	Wrapped		

DESCRIPTION

Hose suitable for transportation of hot steams, smoke and exhaust gases. Low-weight and extremely flexible, good in tight areas. The hose is non-inflammable and has good chemical resistance. Other dimensions are available on request.

Item number	ID	Wp	Vacuum, max	Bend radii [mm]	Coil lenght	Weight
15620016	25 mm	0.15 MPa	5	17 mm	4 m	0.12 kg
15620020	32 mm	0.15 MPa	5	17 mm	4 m	0.14 kg
15620024	38 mm				4 m	0.17 kg
15620029	44 mm	0.15 MPa	0.4	26 mm	4 m	0.21 kg
15620032	51 mm	0.15 MPa	4	30 mm	4 m	0.25 kg
15620040	63 mm	0.13 MPa	4	36 mm	4 m	0.32 kg
15620044	70 mm				4 m	0.36 kg
15620048	76 mm	0.11 MPa	0.3	42 mm	4 m	0.41 kg
15620050	80 mm				4 m	0.44 kg
15620055	89 mm	0.11 MPa	3	49 mm	4 m	0.49 kg
15620060	95 mm				4 m	0.56 kg
15620064	102 mm	0.11 MPa	2	55 mm	4 m	0.65 kg
15620080	127 mm	0.09 MPa	1.7	69 mm	4 m	0.76 kg
15620085	140 mm				4 m	0.9 kg
15620096	152 mm	0.08 MPa	1.4	81 mm	4 m	0.99 kg
15620180	180 mm	0.06 MPa	1	96 mm	4 m	1.21 kg
15620203	203 mm	0.06 MPa	0.7	107 mm	4 m	1.33 kg
15620254	254 mm	0.04 MPa	0.4	132 mm	4 m	1.68 kg

Item number	ID	Wp	Vacuum, max	Bend radii [mm]	Coil lenght	Weight
15620305	305 mm	0.01 MPa	0.3	158 mm	4 m	2.05 kg