



# 5552-02S

## QUICK RELEASE SERIES T



### SPECIFICATIONS

|                                       |          |                      |        |
|---------------------------------------|----------|----------------------|--------|
| <b>Temp min</b>                       | -30 °C   | <b>Safety factor</b> | 1:4    |
| <b>Temp max</b>                       | 100 °C   | <b>Valve type</b>    | Poppet |
| <b>Technical - Material - Quality</b> | AISI 316 |                      |        |

### DESCRIPTION

Nordic range series 525 is a family of quick couplings for hydraulic systems. A manually operated locking ring provides extra security against involuntary disconnection. An extra option for Series 525 couplings and nipples is a pressure eliminator for evacuating residual pressure during connection. Both couplings and nipples are made of steel with Zinc-Nickel surface for maximum durability in tough applications and environments.

| Item number | Standard     | Size 1 | Size 2 |
|-------------|--------------|--------|--------|
| 55520204S   | Nordic range | 1/4"   | 1/4"   |
| 55520206S   | Nordic range | 3/8"   | 3/8"   |
| 55520208S   | Nordic range | 1/2"   | 1/2"   |
| 55520212S   | Nordic range | 3/4"   | 3/4"   |
| 55520216S   | Nordic range | 1"     | 1"     |
| 55520224S   | Nordic range | 1 1/2" | 1 1/2" |