



5601-02

BONDED SEALS MM



SPECIFICATIONS

| | | | |
|-----------------|--------|-----------------|--------|
| Material | NBR | Temp max | 110 °C |
| Temp min | -30 °C | | |

DESCRIPTION

Bonded seals mm are high-performance sealing components made from durable Viton material, ensuring reliable operation within a temperature range of -30°C to 110°C. Designed as coupling spare parts, they provide excellent resistance to heat and chemicals, making them ideal for demanding sealing applications.

| Item number | Thread type 1 | Size 1 | Material |
|-------------|---------------|--------|----------|
| 56010204 | | 4 mm | NBR |
| 56010205 | | 5 mm | NBR |
| 56010206 | | 6 mm | NBR |
| 56010208 | | 8 mm | NBR |
| 56010210 | | 10 mm | NBR |
| 56010212 | | 12 mm | NBR |
| 56010214 | | 14 mm | NBR |
| 56010216 | | 16 mm | NBR |
| 56010218 | | 18 mm | NBR |
| 56010220 | | 20 mm | NBR |
| 56010222 | | 22 mm | NBR |
| 56010224 | | 24 mm | NBR |
| 56010226 | M | 26 mm | NBR |
| 56010227 | | 27 mm | NBR |
| 56010228 | | 28 mm | NBR |
| 56010230 | | 30 mm | NBR |
| 56010233 | | 33 mm | NBR |
| 56010236 | | 36 mm | NBR |
| 56010238 | | 38 mm | NBR |
| 56010245 | | 45 mm | NBR |

| Item number | Thread type 1 | Size 1 | Material |
|-------------|---------------|--------|----------|
| 56010252 | | 52 mm | NBR |