



7623-xx

J WE - U ELBOW



SPECIFICATIONS

Type 1	Male	Shape	90°
Type 2	Male	Material	Steel
Connection 2 - Sealing	O-ring	Standard	ISO 8434-2

DESCRIPTION

The J WE - U is an adjustable coupling adapter from the Coupling - Adapter ORFS and JIC family. Crafted from durable steel, it features a 90° shape and utilizes an O-ring sealing connection, ensuring reliable performance and secure fittings in various industrial applications.

Item number	Pipe dim. 1	Size 1	Size 2	Wp	Weight
76230707	6 mm	UNF 7/16"-20 Male	UNF 7/16"-20 Male	40 MPa	0.03 kg
76230708	6 mm	UNF 7/16"-20 Male	UNF 1/2"-20 Male	40 MPa	0.05 kg
76230709	6 mm	UNF 7/16"-20 Male	UNF 9/16"-18 Male	40 MPa	0.07 kg
76230808	8 mm	UNF 1/2"-20 Male	UNF 1/2"-20 Male	40 MPa	0.05 kg
76230907	10 mm	UNF 9/16"-18 Male	UNF 7/16"-20 Male	40 MPa	0.05 kg
76230909	10 mm	UNF 9/16"-18 Male	UNF 9/16"-18 Male	40 MPa	0.06 kg
76230912	10 mm	UNF 9/16"-18 Male	UNF 3/4"-14 Male	40 MPa	0.12 kg
76230914	10 mm	UNF 9/16"-18 Male	UNF 7/8"-14 Male	40 MPa	0.15 kg
76231209	12 mm	UNF 3/4"-16 Male	UNF 9/16"-18 Male	40 MPa	0.09 kg
76231212	12 mm	UNF 3/4"-16 Male	UNF 3/4"-14 Male	35 MPa	0.11 kg
76231214	12 mm	UNF 3/4"-16 Male	UNF 7/8"-14 Male	35 MPa	0.16 kg
76231217	12 mm	UNF 3/4"-16 Male	UN 1 1/16"-12 Male	35 MPa	0.25 kg
76231412	14, 15, 16 mm	UNF 7/8"-14 Male	UNF 3/4"-14 Male	35 MPa	0.14 kg
76231414	14, 15, 16 mm	UNF 7/8"-14 Male	UNF 7/8"-14 Male	35 MPa	0.19 kg
76231417	14, 15, 16 mm	UNF 7/8"-14 Male	UN 1 1/16"-12 Male	35 MPa	0.26 kg
76231421	14, 15, 16 mm	UNF 7/8"-14 Male	UN 1 5/16"-12 Male	31.5 MPa	0.01 kg
76231712	18, 20 mm	UN 1 1/16"-12 Male	UNF 3/4"-14 Male	35 MPa	0.28 kg
76231714	18, 20 mm	UN 1 1/16"-12 Male	UNF 7/8"-14 Male	35 MPa	0.24 kg
76231717	18, 20 mm	UN 1 1/16"-12 Male	UN 1 1/16"-12 Male	35 MPa	0.32 kg
76231721	18, 20 mm	UN 1 1/16"-12 Male	UN 1 5/16"-12 Male	31.5 MPa	0.41 kg

Item number	Pipe dim. 1	Size 1	Size 2	Wp	Weight
76231726	18, 20 mm	UN 1 1/16"-12 Male	UN 1 5/8"-12 Male	25 MPa	0.7 kg
76232114	25 mm	UN 1 5/16"-12 Male	UNF 7/8"-14 Male	28 MPa	0.36 kg
76232117	25 mm	UN 1 5/16"-12 Male	UN 1 1/16"-12 Male	28 MPa	0.41 kg
76232121	25 mm	UN 1 5/16"-12 Male	UN 1 5/16"-12 Male	28 MPa	0.4 kg
76232126	25 mm	UN 1 5/16"-12 Male	UN 1 5/8"-12 Male	25 MPa	0.67 kg
76232621	30, 32 mm	UN 1 5/8"-12 Male	UN 1 5/16"-12 Male	28 MPa	0.65 kg
76232626	30, 32 mm	UN 1 5/8"-12 Male	UN 1 5/8"-12 Male	25 MPa	0.76 kg
76233030	38 mm	UN 1 7/8"-12 Male	UN 1 7/8"-12 Male	20 MPa	1.03 kg