



7632-xx

J UE ADJUSTABLE 45 ELBOW FITTING – BSP-THREAD



SPECIFICATIONS

Type 1	Male	Shape	45°
Type 2	Male	Material	Steel
Connection 2 - Sealing	O-ring and washer	Standard	ISO 8434-2

DESCRIPTION

The J UE Adjustable 45 Elbow fitting features a 45° coupling design with BSP-thread connection, crafted from durable steel for reliable performance. Its adjustable coupling and O-ring with washer sealing ensure a secure, leak-resistant fit. Part of the Coupling - Adapter ORFS and JIC family, this fitting combines strength and flexibility for versatile hydraulic applications.

SKU	Pipe dim. 1	Size 1	Size 2	Wp	Weight
76320702	6 mm	UNF 7/16"-20 Male	G 1/8" Male	20 MPa	0.03 kg
76320704	6 mm	UNF 7/16"-20 Male	G 1/4" Male	20 MPa	0.04 kg
76320802	8 mm	UNF 1/2"-20 Male	G 1/8" Male	20 MPa	0.04 kg
76320804	8 mm	UNF 1/2"-20 Male	G 1/4" Male	20 MPa	0.05 kg
76320904	10 mm	UNF 9/16"-18 Male	G 1/4" Male	20 MPa	0.05 kg
76320906	10 mm	UNF 9/16"-18 Male	G 3/8" Male	20 MPa	0.08 kg
76320908	10 mm	UNF 9/16"-18 Male	G 1/2" Male	20 MPa	0.12 kg
76321204	12 mm	UNF 3/4"-16 Male	G 1/4" Male	20 MPa	0.1 kg
76321206	12 mm	UNF 3/4"-16 Male	G 3/8" Male	20 MPa	0.09 kg
76321208	12 mm	UNF 3/4"-16 Male	G 1/2" Male	20 MPa	0.25 kg
76321406	14, 15, 16 mm	UNF 7/8"-14 Male	G 3/8" Male	20 MPa	0.12 kg
76321408	14, 15, 16 mm	UNF 7/8"-14 Male	G 1/2" Male	20 MPa	0.14 kg
76321412	14, 15, 16 mm	UNF 7/8"-14 Male	G 3/4" Male	20 MPa	0.23 kg
76321708	18, 20 mm	UN 1 1/16"-12 Male	G 1/2" Male	20 MPa	0.18 kg

SKU	Pipe dim. 1	Size 1	Size 2	Wp	Weight
76321712	18, 20 mm	UN 1 1/16"-12 Male	G 3/4" Male	20 MPa	0.26 kg
76321716	18, 20 mm	UN 1 1/16"-12 Male	G 1" Male	20 MPa	0.34 kg
76322112	25 mm	UN 1 5/16"-12 Male	G 3/4" Male	20 MPa	0.35 kg
76322116	25 mm	UN 1 5/16"-12 Male	G 1" Male	20 MPa	0.37 kg
76322120	25 mm	UN 1 5/16"-12 Male	G 1 1/4" Male	16 MPa	0.53 kg
76322620	30, 32 mm	UN 1 5/8"-12 Male	G 1 1/4" Male	16 MPa	0.57 kg
76323024	38 mm	UN 1 7/8"-12 Male	G 1 1/2" Male	16 MPa	0.74 kg