



# 7723-xx

## ADJUSTABLE 90° ELBOW FITTING UNF THREAD



### SPECIFICATIONS

<b>Type 1</b>	Male	<b>Shape</b>	90°
<b>Type 2</b>	Male	<b>Material</b>	Steel
<b>Connection 2 - Sealing</b>	O-ring	<b>Standard</b>	ISO 8434-3

### DESCRIPTION

The Adjustable 90° elbow fitting with UNF thread is a steel coupling designed for reliable connection in fluid systems. Featuring male connections on both ends with O-ring sealing on the second connection, it ensures secure and leak-resistant joints. Its adjustable design allows precise alignment within the Coupling - Adapter ORFS and JIC family, combining durability and flexibility for demanding applications.

Item number	Pipe dim. 1	Size 1	Size 2	Wp	Weight
77230407	6 mm	UNF 9/16"-18 Male	UNF 7/16"-20 Male	40 MPa	0.06 kg
77230409	6 mm	UNF 9/16"-18 Male	UNF 9/16"-18 Male	40 MPa	0.11 kg
77230412	6 mm	UNF 9/16"-18 Male	UNF 3/4"-16 Male	40 MPa	0.12 kg
77230607	8, 10 mm	UN 11/16"-16 Male	UNF 7/16"-20 Male	40 MPa	0.1 kg
77230609	8, 10 mm	UN 11/16"-16 Male	UNF 9/16"-18 Male	40 MPa	0.1 kg
77230612	8, 10 mm	UN 11/16"-16 Male	UNF 3/4"-16 Male	40 MPa	0.14 kg
77230614	8, 10 mm	UN 11/16"-16 Male	UNF 7/8"-14 Male	40 MPa	0.25 kg
77230617	8, 10 mm	UN 11/16"-16 Male	UN 1 1/16"-12 Male	40 MPa	0.32 kg
77230809	12 mm	UN 13/16"-16 Male	UNF 9/16"-18 Male	40 MPa	0.11 kg
77230812	12 mm	UN 13/16"-16 Male	UNF 3/4"-16 Male	40 MPa	0.12 kg
77230814	12 mm	UN 13/16"-16 Male	UNF 7/8"-14 Male	40 MPa	0.28 kg
77230817	12 mm	UN 13/16"-16 Male	UN 1 1/16"-12 Male	40 MPa	0.38 kg
77231012	14, 15, 16 mm	UNS 1"-14 Male	UNF 3/4"-16 Male	40 MPa	0.24 kg
77231014	14, 15, 16 mm	UNS 1"-14 Male	UNF 7/8"-14 Male	40 MPa	0.26 kg
77231017	14, 15, 16 mm	UNS 1"-14 Male	UN 1 1/16"-12 Male	40 MPa	0.38 kg
77231212	18, 20 mm	UN 1 3/16"-12 Male	UNF 3/4"-16 Male	40 MPa	0.28 kg
77231214	18, 20 mm	UN 1 3/16"-12 Male	UNF 7/8"-14 Male	40 MPa	0.34 kg
77231217	18, 20 mm	UN 1 3/16"-12 Male	UN 1 1/16"-12 Male	40 MPa	0.41 kg
77231221	18, 20 mm	UN 1 3/16"-12 Male	UN 1 5/16"-12 Male	40 MPa	0.55 kg

Item number	Pipe dim. 1	Size 1	Size 2	Wp	Weight
77231617	22, 25 mm	UN 1 7/16"-12 Male	UN 1 1/16"-12 Male	40 MPa	0.55 kg
77231619	22, 25 mm	UN 1 7/16"-12 Male	UN 1 3/16"-12 Male	40 MPa	0.54 kg
77231621	22, 25 mm	UN 1 7/16"-12 Male	UN 1 5/16"-12 Male	40 MPa	0.56 kg
77231626	22, 25 mm	UN 1 7/16"-12 Male	UN 1 5/8"-12 Male	25 MPa	0.67 kg
77232021	28, 30, 32 mm	UN 1 11/16"-12 Male	UN 1 1/16"-12 Male	25 MPa	0.62 kg
77232026	28, 30, 32 mm	UN 1 11/16"-12 Male	UN 1 5/8"-12 Male	25 MPa	0.71 kg
77232430	38 mm	UN 2"-12 Male	UN 1 7/8"-12 Male	20 MPa	1.05 kg