



# 7744-xx

## ADJUSTABLE L-FITTING ORFS – ORFS – BSP THREAD



### SPECIFICATIONS

<b>Type 1</b>	Male	<b>Shape</b>	L
<b>Type 2</b>	Male	<b>Material</b>	Steel
<b>Type 3</b>	Male	<b>Standard</b>	ISO 8434-3
<b>Connection 3 - Sealing</b>	O-ring washer		

### DESCRIPTION

The Adjustable L-fitting ORFS features a durable steel construction designed for reliable performance in hydraulic systems. Belonging to the Coupling - Adapter ORFS and JIC family, this adjustable L-shaped fitting offers three male BSP thread connections, with the third connection sealed by an O-ring washer to ensure leak-free operation.

Item number	Pipe dim. 1	Size 1	Pipe dim. 2	Size 2	Size 3	Wp	Weight
77440404	6 mm	UNF 9/16"-18 Male	6 mm	UNF 9/16"-18 Male	G 9/16"-18 Male	20 MPa	0.13 kg
77440606	8, 10 mm	UN 11/16"-16 Male	8, 10 mm	UN 11/16"-16 Male	G 11/16"-16 Male	20 MPa	0.14 kg
77440806	12 mm	UN 13/16"-16 Male	12 mm	UN 13/16"-16 Male	G 13/16"-16 Male	20 MPa	0.14 kg
77440808	12 mm	UN 13/16"-16 Male	12 mm	UN 13/16"-16 Male	G 13/16"-16 Male	20 MPa	0.33 kg
77441008	14, 15, 16 mm	UNS 1"-14 Male	14, 15, 16 mm	UNS 1"-14 Male	G 1"-14 Male	20 MPa	0.3 kg
77441212	18, 20 mm	UN 1 3/16"-12 Male	18, 20 mm	UN 1 3/16"-12 Male	G 1 3/16"-12 Male	20 MPa	0.44 kg
77441616	22, 25 mm	UN 1 7/16"-12 Male	22, 25 mm	UN 1 7/16"-12 Male	G 1 7/16"-12 Male	20 MPa	0.69 kg